

REAR LOADER COMPACTOR

LEGEND L



For more information



- + Maximum versatility to meet Singapore's requirement
- + Internal width of tailgate: 2200mm
- + Compacting cylinders not in contact with the waste
- + Proportional distributor for smooth movements of the bin lifter unit
- + Maximum containment of sewage
- + Pre-hooking binlifter system with certain grip

Legend L is the **evolution of the rear loader compactor** with tailgate representing the basis of every organised collection service and the solution to **meet a wide range of collection service needs**. It can be used both as a collection station and active and passive collection vehicle, thanks to the many configurations available and the large loading mouth guaranteeing the maximum versatility in the coupling of satellite vehicles. The thrust cylinders of the compacting unit are outside of the hopper and the rods of the compaction blade cylinders face upwards to protect against contact with waste. The rear hopper is designed to easily integrate the various AVC solutions on the market. The proportional oil distributor for the AVC (bin lifter) system speeds up emptying while preserving the integrity of the containers over time; the full height gasket between body and tailgate holds the maximum amount of slurry without narrowing of the body walls; the manual AVC system is fitted with an automatic pre-hooking system with certain grip.




a company of

+BUSIGROUP

OMB TECHNOLOGY S.P.A. - Via delle Brede, 2 - 25080 Paitone (BS) Italy - C.F. / P.I. IT03609770981 - www.ombtechnology.com





REAR LOADER COMPACTOR

LEGEND L



For more information

SPECIFICATIONS	15	19	20	22	26
Body volume (m ³)	15	19	20	22	26
Recommended hopper volume (m ³)	2,5				
Basic bin lifter	DIN connection and comb				
Bin lifter cycle (sec)	11'				
Compaction type system	Articulated single-blade				
Compaction ratio (average)	6:1				
Chassis (axles)	2	3		4	
GVT (ton)	19	28		34	

STANDARD FEATURES

- LED Working lights and beacon lights
- Infrared camera
- Automatic container pre-hooking system
- Sensors of certain hook of the bin
- Unloading cycle from the cabin
- Hardox body floor
- Side door to access the body

MAIN OPTIONAL FEATURES

- Additional hooking arms
- Automatic greasing system
- Waste type selection system
- Lowered hydraulic rear movable flap
- Emergency quick couplings
- Additional sewage collection tanks
- + B Connect System



a company of

+BUSIGROUP

OMB TECHNOLOGY S.P.A. - Via delle Brede, 2- 25080 Paitone (BS) Italy- C.F. / P.I. IT03609770981- www.ombtechnology.com

